



区域 Zoning	编号 Code	品名 Discription	光源 Light Source	电压 (V) Voltage	功率 (W) Unit Watts	单位 Units	一层	总功率 Total Load	品牌型号 Brand & Series	备注 Remarks
公共区域一层	LL1	LED灯带 LED Strip Light	LED 10W/M/2300K	24	10	m.	284	2840	LUCI POWER FLEX CLFT 10	
	LL3	冷阴极管	60W/M/2800K	220	60	m.	780	46800	蔡祖泉	
	LL6	LED灯带 LED Strip Light	LED 6W/M/2300K	24	6	m.	8	48		
	DL2	嵌入式筒灯 Recessed Downlight	MR16 50W/FL	12	50	ea.	26	1300	SKYLUX SK-2821	
	DL3	嵌入式筒灯 Recessed Downlight	MR11 35W/FL	12	35	ea.	14	490	SKYLUX SK-2805	
	DL5	嵌入式筒灯 Recessed Downlight	MR11 35W/SP	12	35	ea.	4	140	SKYLUX SK-2805	
	DL6	嵌入式筒灯 Recessed Downlight	LED 3 W	24	3	ea.	143	429		
	UL1	地埋灯	LED 3 W	24	3	ea.	22	66		
	UL2	地埋灯	CDMT 35W/12°	24	35	ea.	16	560	AD 0308004. 000	
	WL1	水池灯 POOL LIGHT	LED 3W	24	3	ea.	54	162	AD 1613530. 000	嵌入式安装
	WL3	水池灯 POOL LIGHT	LED 3W	24	3	ea.	57	171		表面安装
	AL3	嵌入式可调筒灯 Recessed Adjustable Downlight	MR16 50W/SP	12	50	ea.	32	1600	SKYLUX SK-2822	
	AL4	嵌入式可调筒灯 Recessed Adjustable Downlight	MR16 50W/FL	12	50	ea.	66	3300	SKYLUX SK-2822	
	AL6	嵌入式可调筒灯 Recessed Adjustable Downlight	PAR38 100W	220	100	ea.	42	4200	SKYLUX SK-2867	
	AL7	嵌入式双头筒灯 Recessed Adjustable Downlight	MR16 50WX2/FL	12	100	ea.	43	4300	SKYLUX SK-9501	
	AL8	嵌入式三头筒灯 Recessed Adjustable Downlight	MR11 100X2/10° +CDMT 70W/10° /3000K	220	270	ea.	44	11880		
		吊灯	预留电源 6000W	220	6000	ea.	1	6000	由室内设计师决定	
		吊灯	预留电源 2000W	220	2000	ea.	1	2000	由室内设计师决定	
		吊灯	预留电源 1000W	220	1000	ea.	1	1000	由室内设计师决定	
		吊灯	预留电源 500W	220	500	ea.	7	3500	由室内设计师决定	
		落地灯	预留电源 200W	220	200	ea.	20	4000	由室内设计师决定	
		壁灯	预留电源 500W	220	500	ea.	2	1000	由室内设计师决定	
		壁灯	预留电源 60W	220	60	ea.	2	120	由室内设计师决定	
		台灯	预留电源 60W	220	60	ea.	16	960	由室内设计师决定	

96866 W

Note:
1、灯具尺寸以实际样品为准。
2、T5长度分为600mm/900mm/1200mm，安装时需要交错以避免产生阴影。
3、承包商需提供样品及施工详图以供审核。